

TIEWS NOT WANTED - CROSS COT				
	MIL. SPECS APPLICABLE: Yes No	22.	SERVICE BRAKES: FRONT REAR:	
1.	COMMERCIAL MIL. SPECS:	23.	BRAKE DRUMS: FRONT: ☐ REAR: ☐	
2.	ROAD SURFACE:	24.	HUBS: FRONT: ☐ REAR: ☐	
3.	TOWING SPEED: M.P.H. MAX.		HUBS. FRUNT. REAR.	
4.	WHEELBASE:	0.5	PARKING BRAKE LINKAGE: A DIM	
5.	TURNING CRAMPING ANGLE: 40☐ OR SPL☐	25.	B. DIM C DIM D DIM E DIM See Catalog Brake Linkage Section	
6.	DISTANCE TO FRONT AXLE TO FRONT OF FRAME:			
7.	FRAME BETWEEN TIRES:UNDER TIRES OVER TIRES	26.	SERVICE BRAKE ACTUATING KIT:	
		27.	HYD. LINE & FTG KIT:	
8.	DRAWBAR LATCH: YES. ☐ NO ☐	28.	DRAWBAR: OR SPL.	
9.	CAP. STEERING AXLE: LBS.	29.	PAINT: PRIME PER MIL-P-8585 A ONLY□	
10.	CAP. REAR AXLE: LBS.		SPECIAL FEATURES ACCESSORIES:	
11.	TIRE SIZE: PLY.	30.	or Low Liver States to See See States.	
12.	TRACK: INCHES.	00.		
13.	FRAME WIDTH: OUTSIDE DIM		RUNNING GEAR WILL BE USED ON:	
14.	OVERALL WIDTH: OUTSIDE TIRES:			
15.	TONGUE LENGTH:			
16.	SPRING CTRS: FRONT ☐ REAR ☐	(SPECIFY TYPE OF EQUIPMENT) EXPECT TO USEQUANTITIES OF THESE UNITS DELIVERIES AS FOLLOWS:		
17.	AXLE SIZE TYPE: FRONT ☐ REAR ☐			
18.	SPRING: FRONT REAR MOUNTING: OVER UNDER AXLE			
19.	SPRING FITTINGS FRONT ☐ REAR ☐			
20.	WHEELS			
21.	PARKING BRAKES: FRONT REAR			